

**GAFFELKROKAR GRADE 80**

TILLVERKADE ENLIGT EN 1677-4, PULVER LACKERADE I GULT, SÄKERHETSAKTOR 1:4.
CERTIFIERADE ENLIGT EN-10204 3.1 (KEMISKA OCH MEKANISKA EGENSKAPER).

SPÄRRKROK MED GAFFEL EN 1677-2, TYP EK-12

ART-NR	KÄTTING DIA	INNER HÖJD	GAPÖPPNING SPÄRR	WLL TON	CA KG/ST	ANTAL PER FÖRP
903206	6 MM	75,3	23,5	1,12	0,33	20
903208	7+8 MM	86	22	2	0,53	15
903210	10 MM	104	30	3,15	0,98	10
903213	13 MM	128	37,5	5,3	1,81	5
903216	16 MM	148,3	46,5	8	3,54	4

**FÖRKORTNINGSKROK MED GAFFEL EN 1677-1, TYP EK-86**

ART-NR	KÄTTING DIA	INNER HÖJD	GAPÖPPNING	WLL TON	KG/ST	ANTAL PER FÖRP
903908	7+8 MM	53	10,5	2	0,32	20
903910	10 MM	75	13	3,15	0,73	10
903913	13 MM	92	16,5	5,3	1,60	5
903916	16 MM	99	19	8,0	2,80	4

**SÄKERHETSKROK MED GAFFEL EN 1677-3, TYP EK-738**

ART-NR	KÄTTING DIA	INNER HÖJD	GAPÖPPNING SPÄRR	WLL TON	KG/ST	ANTAL PER FÖRP
903606	6 MM	99	28	1,12	0,45	26
903608	7+8 MM	119	35	2	0,85	26
903610	10 MM	142	45	3,15	1,48	14
903613	13 MM	179	52,5	5,3	2,85	6
903616	16 MM	225	63	8	6,00	3

**GRÄVMASKINSKROK EN 13155, TYP EK-19, SÄKERHETSAKTOR 1:4**

ART-NR	INNER HÖJD	GAPÖPPNING SPÄRR	WLL TON	KG/ST	ANTAL PER FÖRP
903802	66	26	2	0,87	4
903803	75	30	3	1,27	4
903805	98	32,5	5	2,70	4
903808	99	31	8	3,50	2
903810	140	39	10	5,20	2

**BLÅLACKERAD CLEVIS TYP C-KROK FÖR LASTSÄKRING, TYP EK-71**

ART-NR	KÄTTING DIA	TOTAL HÖJD	GAPÖPPNING	MBL TON	KG/ST	ANTAL PER FÖRP
903709	9 MM	152	38	10	0,5	30
903711	11 MM	174	45	15	0,9	25
903713	13 MM	200	52	20	1,4	20



ART-NR	DIM	ST PER PLASTPÅSE
903206X	6-8	10
903208X	7/8-8	10
903210X	10-8	10
903213X	13-8	10
903216X	16-8	10



ART-NR	ST PER PLASTPÅSE
903606X	10
903608X	10
903610X	10
903613X	10
903616X	10
903620X	10
903622X	10



GJUTAD REPERATIONS SET FÖR EK-12

ART-NR	DIM	ST PER PLASTPÅSE
903206XNY	6-8	10
903208XNY	7/8-8	10
903210XNY	10-8	10
903213XNY	13-8	5
903216XNY	16-8	4

GJUTAD REP. SET FÖR GRÄVMASKINSKROK

ART-NR	ST PER PLASTPÅSE
903802X	3
903803X	3
903805X	3
903808X	3
903810X	3