



KROKAR MED ÖGA GRADE 80

TILLVERKADE ENLIGT EN 1677-4, PULVER LACKERADE I GULT, SÄKERHETSFAKTOR 1:4.
CERTIFIERADE ENLIGT EN-10204 3.1 (KEMISKA OCH MEKANISKA EGENSKAPER).

SPÄRRKROK MED ÖGA EN 1677-2, TYP EK-13

ART-NR	KÄTTING	INNER HÖJD	GAPÖPPNING SPÄRR	WLL TON	KG/ST	ANTAL
	DIA					PER FÖRP
903306	6 MM	80	20,5	1,12	0,25	20
903308	7+8 MM	98,5	26	2,0	0,40	20
903310	10 MM	120	26	3,15	0,90	18
903313	13 MM	152	37	5,3	1,94	9
903316	16 MM	185,5	40	8	2,89	6
903320	20 MM	219	43	12,5	5,80	3
903322	22 MM	241	68	15	9,20	2
903326	26 MM	279	82	21,2	13,10	2
903332	32 MM	355	100	31,5	20,09	1



FÖRKORTNINGSKROK MED ÖGA EN 1677-1, TYP EK-85

ART-NR	KÄTTING	INNER HÖJD	GAPÖPPNING	WLL TON	KG/ST	ANTAL
	DIA					PER FÖRP
903406	6 MM	47	8	1,12	0,14	20
903408	7+8 MM	61,5	11	2,0	0,25	20
903410	10 MM	80	13,0	3,15	0,65	20
903413	13 MM	99,7	16,5	5,3	1,39	15
903416	16 MM	106,5	19,0	8	2,20	8
903420	20 MM	140	24	12,5	4,60	3
903422	22 MM	165	28,0	15	8,20	2
903426	26 MM	197	30	21,2	9,80	2



SÄKERHETSKROK MED ÖGA EN 1677-3, TYP EK-737

ART-NR	KÄTTING	INNER HÖJD	GAPÖPPNING SPÄRR	WLL TON	KG/ST	ANTAL
	DIA					PER FÖRP
903506	6 MM	110	32	1,12	0,50	20
903508	7+8 MM	136	40	2,0	0,83	26
903510	10 MM	168	48	3,15	1,42	14
903513	13 MM	206	57	5,3	2,86	6
903516	16 MM	254	65	8,00	5,90	3
903520	20 MM	278	82	12,5	8,50	2
903522	22 MM	319	80	15,00	11,60	2
903526	26 MM	362	109	21,2	18,00	1
903532	32 MM	470	131	31,50	46,00	1



SÄKERHETSKROK MED ÖGA OCH SVIVEL EN 1677-3, TYP EK-755

ART-NR	KÄTTING	INNER HÖJD	GAPÖPPNING SPÄRR	WLL TON	KG/ST	ANTAL
	DIA					PER FÖRP
904908	7+8 MM	189	40	2,0	1,21	10
904910	10 MM	223	48	3,15	1,98	10
904913	13 MM	267	57	5,3	3,59	6
904916	16 MM	339	65	8,00	7,27	3



GJUTERI KROK EN 1677-2, TYP EK-116

ART-NR	KÄTTING	INNER HÖJD	GAPÖPPNING	MBL TON	KG/ST	ANTAL
	DIA					PER FÖRP
901008	7+8 MM	118	62	2,0	0,71	20
901010	10 MM	152	73	3,20	1,36	12
901013	13 MM	180	90	5,3	2,57	6
901016	16 MM	212	105	8,00	3,96	4



SPÄRRKROK MED ÖGA OCH SVIVEL EN 1677-2, TYP EK-040

ART-NR	KÄTTING	INNER HÖJD	GAPÖPPNING		WLL TON	KG/ST	ANTAL
	DIA		SPÄRR				PER FÖRP
904010	10 MM	162,5	26		3,15	1,25	15
904013	13 MM	191	32,5		5,3	2,33	10
904016	16 MM	243,5	43		8	4,02	5
904020	19+20 MM	276,5	49,5		12,5	7,05	2
904022	22 MM	332	54,5		15	12,67	2

**SPÄRRKROK MED ÖGA, SVIVEL, OCH KULLAGER EN 1677-2, EK-788**

ART-NR	KÄTTING	INNER HÖJD	GAPÖPPNING		WLL TON	KG/ST	ANTAL
	DIA		SPÄRR				PER FÖRP
900206	6 MM	138	24		1,12	0,65	20
900208	7+8 MM	170	28,5		2	0,95	16
900210	10 MM	207	31		3,15	1,71	14
900213	13 MM	248	40		5,3	3,13	6
900216	16 MM	295	45		8	5,44	3
900220	20 MM	356	56		12,5	9,5	1
922222	22 MM	441	70		15	16	1

**GJUTEN REPARATIONS SET FÖR EK-13**

ART-NR	ST PER PÅSE
903306 X	10
903308 X	10
903310 X	10
903313 X	10
903316 X	10
903320 X	5
903322 X	4
903326 X	4
903332 X	4

**REPARATIONS SET FÖR SÄKERHETSKROKAR**

ART-NR	ST PER PLASTPÅSE
903608 X	10
903610 X	10
903613 X	10
903616 X	10
903620 X	10
903622 X	10

