

**ÖGLOR OCH KOPPLINGSLÄNKAR GRADE 80**

TILLVERKADE ENLIGT EN 1677-4, PULVER LACKERADE I GULT, SÄKERHETSFAKTOR 1:4.

CERTIFIERADE ENLIGT EN-10204 3.1 (KEMISKA OCH MEKANISKA EGENSKAPER).

TOPPÖGLA/MASTER LINK EN 1677-4, TYP EK-33

| ART-NR | DIM | GODS | | INVÄNDIG | | KG/ST | ANTAL PER FÖRP |
|--------|--------|-------|--------|----------|-------|-------|----------------|
| | | DIA | WLL | HÖJD | BREDD | | |
| 904313 | 76-8 | 13 MM | 1,6 T | 110 | 60 | 0,40 | 20 |
| 904316 | 87-8 | 16 MM | 2,12 T | 110 | 60 | 0,54 | 20 |
| 904319 | 108-8 | 18 MM | 3,15 T | 135 | 75 | 0,83 | 15 |
| 904322 | 1310-8 | 22 MM | 5,3 T | 160 | 90 | 1,50 | 10 |
| 904325 | 1613-8 | 26 MM | 8 T | 180 | 100 | 2,10 | 8 |
| 904332 | 1816-8 | 32 MM | 11,2 T | 200 | 110 | 3,95 | 4 |
| 904336 | 2018-8 | 36 MM | 14 T | 260 | 140 | 6,34 | 2 |
| 904340 | 2220-8 | 40 MM | 17 T | 300 | 160 | 8,96 | 2 |
| 904345 | 2622-8 | 45 MM | 21,2 T | 340 | 180 | 12,80 | 2 |

**TOPPÖGLA EN 1677-4, TYP EK-32**

| ART-NR | DIM | WLL T | MASTER LINK | BALANS ÖGLOR | | KG/ST | ANTAL PER FÖRP |
|--------|------|--------|-------------|--------------|----------|-------|----------------|
| | | | | HÖJD | BREDD | | |
| 904516 | 6-8 | 2,36 T | 135 X 75 | 13 MM | 54 X 25 | 1,26 | 10 |
| 904520 | 7-8 | 3,15 T | 135 X 75 | 13 MM | 60 X 38 | 1,32 | 8 |
| 904522 | 8-8 | 4,25 T | 160 X 90 | 16 MM | 70 X 34 | 2,2 | 8 |
| 904528 | 10-8 | 6,7 T | 180 X 100 | 18 MM | 85 X 40 | 3,22 | 4 |
| 904532 | 13-8 | 11,2 T | 200 X 110 | 22 MM | 115 X 50 | 6,1 | 2 |
| 904538 | 16-8 | 17 T | 260 X 140 | 26 MM | 140 X 65 | 9,67 | 1 |

**TOPPÖGLA STOR TYP MED STORA BALANS ÖGLOR, EN 1677-4, TYPE EK-488**

| ART-NR | DIM | WLL T | MASTER LINK | BALANS ÖGLOR | | KG/ST | ANTAL PER FÖRP |
|--------|------|--------|-------------|--------------|-----------|-------|----------------|
| | | | | HÖJD | BREDD | | |
| 907528 | 10-8 | 9,4 T | 190 X 110 | 20 MM | 160 X 95 | 4,87 | 4 |
| 907532 | 13-8 | 14,2 T | 230 X 130 | 25 MM | 190 X 110 | 8,98 | 2 |
| 907538 | 16-8 | 22,3 T | 275 X 150 | 30 MM | 230 X 130 | 15,28 | 1 |

**TOPPÖGLA/MASTERLINK EN 1677-4, TYP EK-95**

| ART-NR | DIM | GODS | | INVÄNDIG | | KG/ST | ANTAL PER FÖRP |
|--------|--------|-------|------|----------|-------|-------|----------------|
| | | DIA | WLL | HÖJD | BREDD | | |
| 905813 | 76-8 | 13 MM | 2,7 | 115 | 60 | 0,35 | 20 |
| 905816 | 87+8-8 | 16 MM | 4,1 | 120 | 70 | 0,60 | 20 |
| 905820 | 10-8 | 20 MM | 6,7 | 150 | 80 | 1,10 | 15 |
| 905822 | 1310-8 | 22 MM | 8,2 | 170 | 90 | 1,53 | 10 |
| 905825 | 1613-8 | 25 MM | 10,7 | 190 | 100 | 2,21 | 6 |
| 905828 | 1816-8 | 28 MM | 12,9 | 210 | 110 | 3,06 | 4 |
| 905832 | 19-8 | 32 MM | 17,1 | 270 | 140 | 5,05 | 3 |
| 905838 | 2018-8 | 38 MM | 28,1 | 270 | 140 | 7,30 | 2 |
| 905845 | 2220-8 | 45 MM | 38,3 | 320 | 170 | 12,20 | 2 |
| 905850 | 2622-8 | 50 MM | 45 | 380 | 200 | 17,65 | 2 |
| 905860 | 32-8 | 60 MM | 65,3 | 430 | 220 | 28,85 | 1 |
| 905870 | 36-8 | 70 MM | 84,4 | 500 | 250 | 45,48 | 1 |

**TOPPÖGLA STOR TYP MED STORA BALANS ÖGLOR, EN 1677-4, TYPE EK-96**

| ART-NR | DIM | WLL T | MASTER LINK | BALANS ÖGLOR | | KG/ST | ANTAL PER FÖRP |
|--------|------|-------|-------------|--------------|--------|-------|----------------|
| | | | | HÖJD | BREDD | | |
| 905916 | 6-8 | 4,1 | 120 x 70 | 95 x 51 | 1,19 | 10 | |
| 905920 | 7-8 | 6,5 | 170 x 90 | 120 x 70 | 2,41 | 6 | |
| 905922 | 8-8 | 8,2 | 170 x 90 | 150 x 80 | 3,77 | 5 | |
| 905925 | 9-8 | 10,7 | 190 x 100 | 150 x 80 | 4,45 | 4 | |
| 905928 | 10-8 | 12,9 | 210 x 110 | 170 x 90 | 6,12 | 2 | |
| 905932 | 13-8 | 17,1 | 270 x 140 | 190 x 100 | 9,47 | 2 | |
| 905938 | 16-8 | 28,1 | 270 x 140 | 270 x 140 | 17,40 | 1 | |
| 905945 | 20-8 | 38,3 | 320 x 170 | 270 x 140 | 26,76 | 1 | |
| 905950 | 22-8 | 45 | 380 x 200 | 270 x 140 | 33,20 | 1 | |
| 905960 | 26-8 | 65,3 | 430 x 220 | 380 x 200 | 66,00 | 1 | |
| 905970 | 32-8 | 84,4 | 500 x 250 | 430 x 220 | 103,00 | 1 | |

**KOPPLINGS LÄNK EN 1677-1, TYP EK-74, LACKERAD I GULT FÖR LYFT, LJUSGRÄTT FÖR TRÄLFISKE**

| ART-NR | DIM | WLL 1:4 | BYGG-HÖJD | BREDD ÖPPNING | ANLÄGGS- | | KG/ST | ANTAL PER FÖRP |
|--------|-------|---------|-----------|---------------|----------|-------|-------|----------------|
| | | | | | DIA | BREDD | | |
| 904606 | 6-8 | 1,12 T | 39,0 | 16 | 7 | 0,08 | 20 | |
| 904608 | 7/8-8 | 2 T | 58,0 | 21 | 8,5 | 0,15 | 20 | |
| 904610 | 10-8 | 3,15 T | 69 | 26 | 11,5 | 0,32 | 20 | |
| 904613 | 13-8 | 5,3 T | 85,0 | 30 | 15 | 0,69 | 20 | |
| 904616 | 16-8 | 8 T | 102 | 35 | 19,8 | 1,20 | 20 | |
| 904620 | 20-8 | 12,5 T | 118,0 | 42 | 22 | 1,97 | 10 | |
| 904622 | 22-8 | 15 T | 140 | 50 | 26,8 | 3,07 | 6 | |
| 904626 | 26-8 | 21,2 T | 154,0 | 58 | 30 | 4,68 | 4 | |
| 904632 | 32-8 | 31,5 T | 204 | 68 | 37,0 | 8,75 | 2 | |



RUNDSLINGS KOPPLING EN 1677-1, TYP EK-1

| ART-NR | DIM | WLL 1:4 | BAND- BREDD | BREDD ÖPPNING | ANLÄGGS- DIA | KG/ST | ANTAL PER FÖRP |
|--------|-------|---------|----------------|------------------|-----------------|-------|-------------------|
| 904706 | 6-8 | 1,12 T | 38 | 15,5 | 18 | 0,20 | 20 |
| 904708 | 7/8-8 | 2 T | 38 | 20 | 24 | 0,30 | 20 |
| 904710 | 10-8 | 3,15 T | 45 | 24 | 30,5 | 0,53 | 20 |
| 904713 | 13-8 | 5,3 T | 51 | 28,5 | 36,8 | 1,03 | 14 |
| 904716 | 16-8 | 8 T | 63 | 35 | 45,2 | 1,87 | 10 |

**OMEGA KOPPLING EN1677-1, TYP EK-2**

| ART-NR | DIM | WLL 1:4 | GAP- ÖPPNING | BREDD ÖPPNING | BYGG- HÖJD | KG/ST | ANTAL PER FÖRP |
|--------|-------|---------|-----------------|------------------|---------------|-------|-------------------|
| 904808 | 7/8-8 | 2 T | 10 | 23,5 | 35 | 0,22 | 20 |
| 904810 | 10-8 | 3,15 T | 12 | 31,5 | 40,5 | 0,36 | 20 |
| 904813 | 13-8 | 5,3 T | 15 | 41 | 54 | 0,69 | 10 |
| 904816 | 16-8 | 8 T | 19 | 49,5 | 64 | 1,12 | 10 |
| 904819 | 20-8 | 12,5T | 23 | 58 | 75,6 | 2,2 | 5 |

**LÖSA KOPPLINGS BULTAR MED LÅSHYLSA TILL EK-74**

| ART-NR | DIM | ANTAL PER FÖRP |
|----------|-------|-------------------|
| 904608 X | 7/8-8 | 10 |
| 904610 X | 10-8 | 10 |
| 904613 X | 13-8 | 10 |
| 904616 X | 16-8 | 10 |
| 904620 X | 20-8 | 10 |
| 904622 X | 22-8 | 10 |
| 904626 X | 26-8 | 10 |
| 904632 X | 32-8 | 10 |

**LÖSA KOPPLINGS BULTAR MED LÄSSPLINT TILL EK-2 OMEGA KOPPLING**

| ART-NR | DIM | ANTAL PER FÖRP |
|----------|-------|-------------------|
| 904808 X | 7/8-8 | 6 |
| 904810 X | 10-8 | 6 |
| 904813 X | 13-8 | 4 |
| 904816 X | 16-8 | 4 |

